
Scout Group Risk Assessments



Task to be carried out by trained and authorised personnel only or those receiving training and under supervision

Likelihood 1,2,3,4,5. from unlikely to certain. 1,2,3,4,5. from minor injury to death. Severity

Page 1 of 67

sides.

Step No.	Key steps carried out	Associated Hazards	L	S	RR	Preventative Measures: Already present /Additional Needed	Further Action?	By Whei	By Who	New RR
1	Fire emergencies	Inability to identify correct extinguisher for use. Insufficient signage for extinguishers.	3	4	12	Add sign for water (to add) and Co2 extinguisher. Mount Extinguishers on the wall, either side of the double doors.			to the key p sure it is ob- action point	nformation. Stice oints and make vious where you sare and who
2	Using scissors	First Aid injury / Minor injury Possibility of injury from sharp object				Education & Supervision - Participants to be informed that scissors are for cutting of paper only.			needs to ca	rry them out.
3	Using ladders	Ladder Collapse :- Unstable				Use tested & compliant equipment. Inspect equipment prior to use for ware or defect. Short ladders erected by one person, should have the foot of ladder placed against a wall or fixture and	Try to be specific about should work (not just a that something should For example, this might so here it might read 'L	general be in pla t be for E	comment ce) Beavers	
	Create a flow in the document, think about what's most important to highlight. Use headings and categories to help on larger documents.			À		pushed upright from the head. Long ladders, where possible, should be laid flat on the ground, one person at the foot of the ladder with one foot placed at the bottom to brace it against	explain how to hold and safely			
		sure	that its	used c	g make consister	by rung to raise the ladder.	Technical language used			
		throi	ughout t	he doo	cument	rsed sequence to lower. Where rs are being put into locks, they should be laid flat on lock side, lifted by the rungs at the head of the ladder and	prevent some users from understanding the content and therefore what they	nt are		
						gently slid into the lock. Ensure top of ladder is well clear of any cables. The ladder is to be angled against structure at a 75degree or a	needing to do in order to operate to this risk assessment			
						ratio of 4 up to 1 out. Ensure ladder is resting on firm, even ground. Ensure ladder projects at least 1.0m above the				
						landing place, with landing rung level or slightly above the working platform, thus providing a handhold for people getting on and off. If ladder is not long				
						enough for the job – get a longer one!				